

COOKTOPS

GAS
600



Colour:	White	Stainless Steel
Model:	ICS6WG2	ICS6SG2
Dimensions:	585mm (L) x 500 (W) x 30mm (D)	
Cut Out Size:	550mm (L) x 470 (W) x 30mm (D)	
Packaging:	Carton Size	61 cm (H) x 68 cm (W) x 11.5 cm (D)
	Carton Cubic metres	0.047 cubic metres
	Carton Weight	11 kg

Electrical Connection: The appliance is supplied with a 100cm long flexible supply lead with three pin plug attached. The point of attachment is located at the rear and underside of the appliance.

Burners	Gas	Diameter Injectors	Operating Pressure	Burner Rating (MJ)	Pan Diameter (CM)
Front left	Propane	0,92	2,75	10.8	15-26
	Natural	1,50	1,00		
Front Right	Propane	0,53	2,75	3.6	9-16
	Natural	0,88	1,00		
Rear left	Propane	0,70	2,75	6.3	13-18
	Natural	1,16	1,00		
Rear right	Propane	0,70	2,75	6.3	13-18
	Natural	1,16	1,00		

Other:

- Suitable for natural gas and LPG – LPG jets come with appliance.
- A.G.A. Approved
- Gas entry point at rear right underside of appliance
- Automatic under knob ignition
- Enamel pan trivets and burner caps

Method of Installation:

- Cut benchtop to dimensions as shown.
- Position the special sealed gasket (provided) on the edge of the cooktop making sure that the ends meet without one lying on top of the other.
- Put the cooktop in the benchtop opening making sure that it is centered.
- Fasten the hob to the benchtop with the fastening brackets. The traction of the screws will be enough to cut the sealing gasket so that the excess can easily be removed.

Country of Origin: Italy

www.iagappliances.com.au

